all in one, bar graph LED + LCD

MOISTURE METER

Model: MS-7003 *ISO-9001, CE, IEC1010*







The Art of Measurement

Concrete/Wood, Red LED bar graph + LCD display

MOISTURE METER

Model: MS-7003

FEATURES

*	Designed to check the moisture level of wood, concrete,	
	and other non-wood material.	
*	6 % to 40 % moisture range on wood.	
*	0 to 100% relative moisture value for Concrete and	
	other non-wood material.	
*	Red LED bar graph indicator and LCD digital display.	
*	All in one, meter build in the test pins.	
*	Optional separate probe, available for remote	
	measurement.	
*	Microprocessor circuit assures maximum possible	
	accuracy, provides special functions and features.	
*	Records Maximum & Minimum reading with recall.	
*	Data hold function to freeze the desired value on display.	
*	Heavy duty & compact housing case, designed for easy	
	carry out & operation.	
*	Built-in low battery indicator.	
*	With auto power shut off function to prolong the battery	
	battery life.	

SPECIFICATIONS

Applications	Designed to check the moisture level of
	wood, concrete and other non-wood
	material.
Principal	Used the 2 pins electrode to measure the
	conductive ability of the species, then
	converter to the reading of % " Moisture
	of Content ".
Circuit	Custom one-chip of microprocessor LSI
	circuit.
Display	LCD size : 51 mm x 37 mm
	Digit size : 16 mm (0.62 ")

Material/	Material 1 :
Range	0 to 100% relative moisture value for
	Concrete. and other non-wood material.
	Material 2 :
	6 % to 40 % moisture range on wood.
Resolution	0.1 %.
Accuracy	±(5%+5d)
	@ 23± 5 °C
	@ Material 1 : 13 % to 100%
	@ Material 2 : 6 % to 40%
Probe	2 pins moisture electrode.
Data Ho <mark>ld</mark>	By push button on front panel.
Memory Recall	Records Maximum & Minimum reading
	value.
Sampling Time	Approx. 0.8 second.
Operating	0 to 50 $^{\circ}\mathrm{C}$ (32 to 122 $^{\circ}\mathrm{F}$).
Temp./Humidity	Less than 80 %RH.
Power Supply	Alkaline 006P, MN1604 (PP3) DC 9V
	battery.
Power Current	Approx. DC 16 mA.
Weight	251 g/0.55 LB.
Dimension	216.5 x 68.5 x 29.7 mm
	(8.4 x 2.7 x 1.2 inch).
Accessories	Instruction manual1 PC.
Included	Extra contact pins1 Set.
Optional	Separate Probe, MP-31
Accessories	Hard Carrying Case, CA-06
	Soft Carrying Case, CA-05A

^{*} Appearance and specifications listed in this brochure are subject to change without notice.