all in one **Model : PMS-713** *Iso-9001, CE, IEC1010*





The Art of Measurement

all in one **MOISTURE METER**

Model : PMS-713

FEATURES

* Designed to check the moisture level of wood, concrete, and other non-wood material.

^{*} 6 % to 40 % moisture range on wood.

 0 to 100% relative moisture value for Concrete and other non-wood material.

* All in one, meter build in the test pins.

* Data hold function to freeze the desired value on display.

* Microprocessor circuit ensures high accuracy and provides special functions and features.

* Operates from DC 1.5V (UM4/AAA) x 4 PCs batteries.

* Built-in low battery indicator.

* With the pins' protection cover.

 Durable, long-lasting components, enclosed in strong, compact ABS-plastic housing.

Applications	Designed to check the moisture level of wood,
	concrete and other non-wood material.
Measuring	Used the 2 pins electrode to measure the conductive
Principal	ability of the species, then converter to the reading
	of % " Moisture of Content ".
Display	LCD size : 28 mm x 19 mm.
Material/ Range	<i>Material 1</i> : 100% relative moisture value for
	Concrete. and other non-wood material.
	<i>Material 2</i> : 6 % to 40 % moisture range on wood.
Resolution	0.1 %.
Accuracy	± (5% + 5d)
	@ 23± 5 ℃
	@ Material 1 : 13 % to 100%
	@ Material 2 : 6 % to 40%
Circuit	Custom one-chip of microprocessor LSI circuit.
Probe	2 pins moisture electrode.
Data Hold	Freeze the display reading.
Sampling Time	Approx. 0.8 second.
Operating Temp.	0 to 50 ℃.
Operating Humidity	Less than 80% R.H.
Power Supply	DC 1.5 V battery (UM4/AAA) x 4 PCs,
Power Current	Approx. DC 12 mA
Weight	180 g/ 0.40 LB. @ Battery is included.
Dimension	180 x 40 x 40 mm (7.1" x 1.6" x 1.6")
Accessories	Instruction manual1 PC.
Included	Extra test pins1 Set.
Optional	* Soft carrying case with sash
Accessory	(210 x 80 x 50 mm), Model : CA-52A
	* Test pins , MP-02

* Appearance and specifications listed in this brochure are subject to change without notice. 0705-PMS713