



Heavy Duty Differential Pressure Manometer

Wide range dual input With multiple units and RS-232 interface

Features:

- · Dual differential inputs with internal sensors
- Wide (±802 inches of water) measurement range with high resolution
- Displays 8 types of pressure units: mbar, psi, kg/cm², mmHg, inHg, mH₂O, inH₂O, and atm
- Record/Recall MIN and MAX readings
- Data Hold and Auto Power off
- Zero function for offset measurements
- Basic accuracy: ±1% of full scale (includes hysteresis)
- Large dual LCD display
- Metal input connections with two quick-disconnect fittings
- Built-in RS-232 PC interface with optional Data Acquisition software and datalogger
- Includes 2 quick disconnect-fittings, 9V battery, protective rubber holster with stand, and carrying case



Con Car	10
	0

Specifications	Range	Resolution	Basic Accuracy
mbar	±2000mbar	1mbar	±2%FS
psi	±29psi	0.02psi	±1%FS
kg/cm ²	±2.040kg/cm ²	0.001kg/cm ²	±1%FS
mmHg	±1500mmHg	1mmHg	±1%FS
inHg	± 59.05inHg	0.05inHg	±1%FS
mH₂0	±20.40mH ₂ 0	0.01mH ₂ 0	±1%FS
inH₂0	±802.0inH ₂ 0	0.5inH20	±1%FS
atm	±1.974atm	0.001atm	±1%FS
Dimensions	7 x 2.9 x 1.3" (178 x	74 x 33mm)	
Weight	12oz (350g)		

Ordering Information:

407910	Heavy Duty Manometer
407910	-NIST407910 with NIST Certificate
156119	117V AC Adaptor
409997	Soft Vinyl Pouch Carrying Case