KERN **572-35**



All-rounder, e.g. as precision balance in the laboratory or in harsh industrial applications, ideal for the diverse possibilities of Industry 4.0 applications



| Measuring system | | | | |
|--|--|--|--|--|
| Adjustment options: | External calibration | | | |
| Eccentric loading at 1/3 [Max]: | 50 mg | | | |
| Linearity: | 30 mg | | | |
| Readability [d]: | 10 mg | | | |
| Recommended adjusting weight: | 2 kg (F1) | | | |
| Repeatability: | 10 mg | | | |
| Resolution: | 240000 | | | |
| Stabilisation time under laboratory conditions: | 3 s | | | |
| Warm up time: | 2 h | | | |
| Weighing capacity [Max]: | 2,400 kg | | | |
| Weighing system: | Strain gauge | | | |
| Weighing units: | mo tl (Tw) lb tl (Singap. Malays) ffa ct oz ozt tl (HK) kg g dwt | | | |
| Display | | | | |
| Display digit height (large): | 2,100 cm | | | |
| Counting | | | | |
| Counting resolution: | 240000 | | | |
| Mininum piece weight at piece | 10 mg | | | |
| counting (Laboratory: | 10 mg | | | |
| counting (Laboratory: Mininum piece weight at piece counting (Normal): | 100 mg | | | |
| Mininum piece weight at piece | | | | |

| Functions | | | | | |
|--|---|--|--|--|--|
| Counting function: | yes | | | | |
| Percentage determination: | yes | | | | |
| PRE-TARE function: | yes | | | | |
| Vibration-free weighing (Animal weighing program): | yes | | | | |
| Weighing with tolerance range: | yes | | | | |
| Environmental conditions | | | | | |
| Maximum humidity: | 80 % | | | | |
| Maximum operating temperature: | 40 °C | | | | |
| Minimum ambient temperature: | -10 °C | | | | |
| Power supply | | | | | |
| Charging time: | 8 h | | | | |
| Input voltage: | 100 V - 240 V AC 50 / 60 Hz | | | | |
| Mains adapter: | Mains adapter external | | | | |
| Mains adapter/adapter included: | US UK CH EURO | | | | |
| Operating time (Backlight off): | 48 h | | | | |
| Operating time (Backlight on): | 24 h | | | | |
| Rechargeable battery: | Rchrg. battery optional (factory) | | | | |
| | | | | | |
| Services (optional) | | | | | |
| Services (optional) DAkkS Certificate: | 963-127 | | | | |
| | 963-127 | | | | |
| DAkkS Certificate: | 963-127 KERN | | | | |
| DAkkS Certificate: Category | | | | | |
| DAkkS Certificate: Category Brand: | KERN | | | | |
| DAkkS Certificate: Category Brand: Category: | KERN Balances | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: | KERN Balances | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping | KERN Balances Precision balance | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: | KERN Balances Precision balance 24 h | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): | KERN Balances Precision balance 24 h 400 x 340 x 220 mm | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: | KERN Balances Precision balance 24 h 400 x 340 x 220 mm 4,100 kg | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: | KERN Balances Precision balance 24 h 400 x 340 x 220 mm 4,100 kg 2,300 kg | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: | KERN Balances Precision balance 24 h 400 x 340 x 220 mm 4,100 kg 2,300 kg | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction | KERN Balances Precision balance 24 h 400 x 340 x 220 mm 4,100 kg 2,300 kg Parcel service | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: | KERN Balances Precision balance 24 h 400 x 340 x 220 mm 4,100 kg 2,300 kg Parcel service Cast aluminium alloys | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions housing (WxDxH): | KERN Balances Precision balance 24 h 400 x 340 x 220 mm 4,100 kg 2,300 kg Parcel service Cast aluminium alloys 180 x 310 x 85 mm | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions housing (WxDxH): Level indicator: | KERN Balances Precision balance 24 h 400 x 340 x 220 mm 4,100 kg 2,300 kg Parcel service Cast aluminium alloys 180 x 310 x 85 mm yes | | | | |
| DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions housing (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted | KERN Balances Precision balance 24 h 400 x 340 x 220 mm 4,100 kg 2,300 kg Parcel service Cast aluminium alloys 180 x 310 x 85 mm yes stainless steel | | | | |

KERN **572-35**



All-rounder, e.g. as precision balance in the laboratory or in harsh industrial applications, ideal for the diverse possibilities of Industry 4.0 applications

Piktogramme

STANDARD

| CAL EXT | | KCP Protocol | | | % Percent | -√+ ⊙ Ͽッ TOL |
|---------|-------|-----------------|-----|-------|--------------|--------------------|
| | UNDER | B H | DMS | 1 DAY | | |

OPTION

| Ŀ | | • | DAkkS | |
|--------|--------|-----|---------|--|
| EASY-T | RS 232 | USB | +3 DAYS | |

FACTORY

ACCU