# **KERN DAB 200-2**

ideal for recurring rapid tests







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	50 mg
Linearity:	30 mg
Load cell connection:	4-wire
Measuring capacity [Max]:	199 °C
Minimum weight (USP):	20 g
Readability (moisture):	0,050 %
Readability [d]:	10 mg
Repeatability:	10 mg
Resolution:	20000
Stabilisation time under laboratory conditions:	3 s
Tare range:	200 g
Warm up time:	30 min
Weighing capacity [Max]:	200 g
Weighing system:	Strain gauge
Weighing units:	g % Feuchte % Trockenmasse

Display	
Display digit height (large):	1,400 cm
Display digit height (small):	6 mm

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	5°C
Minimum humidity:	5 %

Power supply	
Battery:	no battery
Input voltage:	230 V AC 50 Hz
Mains adapter/adapter included:	EURO

## Services (optional)

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127 Factory calibration certificate 964-305

(temperature):

Category

Brand: **KERN** 

Product Group: Moisture analyser

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	490 x 350 x 360 mm
Gross weight:	7,100 kg
Net weight:	4,820 kg
Shipping method:	Parcel service

Construction	
Level indicator:	yes
Material weighing plate:	Aluminium dish
Overall dimensions mounted (WxDxH):	240 x 365 x 180 mm
Revolving screw feet:	yes
Weighing surface (d):	92

## Piktogramme

#### STANDARD

















#### **OPTION**

